

# WLXTE Wet Location Polycarbonate Exit Sign



<b>Project:</b>	
<b>Type:</b>	
<b>Catalog #:</b>	



## STANDARD

## OPTIONAL



## ILLUMINATION

- Ultra bright, energy efficient, long life Red or Green LEDs.

## ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

## MOUNTING

- Mounting hardware provided for back surface wall mount.

## HOUSING

- 5VA flame retardant, UV-stabilized polycarbonate gray finish.
- High-impact resistant, UV-stabilized polycarbonate clear lens.
- Corrosion-resistant enclosure with engineering grade silicone gasket.
- Knockouts provided for conduit feed applications.
- EZ snap-out Chevron directional indicators.


## OPTIONS

- HTR: Optional internal heater for cold temperature applications.
- USA: Substantial transformation assembly in the U.S. complies with "Assembled in the USA" under the Buy American Act.

## WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for wet locations (10°C – 40°C).
- Certified to CEC under Title 20 Regulations.

## DIMENSIONS



## ORDERING INFORMATION

Sample Part Number: WLXTEREM

Special voltage available.  
Check with your Best  
Lighting Representative.

MODEL	No. of FACES	LETTER COLOR	BATTERY	OPTIONS
WLXTE	(blank) Single Face (standard)	R Red G Green	(blank) AC-Only EM Battery Backup	HTR Internal Heater <sup>1</sup> USA Assembled in USA

<sup>1</sup> Available only with EM units.

<b>Project:</b>	
<b>Type:</b>	
<b>Catalog #:</b>	

## ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
WLXTE/EM	5.4	5.4	0.045	0.019